

# Dimensions



FTC Series

### Overall Dimensions

Model	Volume	Efficiency	Power	Voltage	Pressure	Noise	Dimensions (A x B x H x d)
FTC-H50N	500 m3/h	86-94 %	120 W	220 V	160 Pa	30 dB(A)	1110 x 845 x 260 x 200 mm
FTC-H100N	1000 m3/h	86-91 %	260 W	220 V	170 Pa	36 dB(A)	1143 x 809 x 342 x 200 mm
FTC-H150N	1500 m3/h	85-88 %	285 W	220 V	175 Pa	44 dB(A)	1143 x 809 x 342 x 200 mm
FTC-H200N	2000 m3/h	85-90%	330 W	220 V	205 Pa	48 dB(A)	1150 x 888 x 350 x 250 mm
FTC-H250N	2500 m3/h	85-89%	360 W	220 V	260 Pa	51 dB(A)	1150 x 888 x 350 x 250 mm
FTC-H300N	3000 m3/h	87-91%	480 W	220 V	260 Pa	52 dB(A)	1200 x 904 x 381 x 250 mm
FTC-H350N	3500 m3/h	86-91%	560 W	220 V	265 Pa	55 dB(A)	1200 x 904 x 381 x 250 mm
FTC-H400N	4000 m3/h	86-92%	600 W	220 V	280 Pa	57 dB(A)	1200 x 1160 x 476 x 285~254 mm
FTC-H450N	4500 m3/h	86-91%	780 W	220 V	285 Pa	61 dB(A)	1200 x 1160 x 476 x 285~255 mm
FTC-H500N	5000 m3/h	86-90%	900 W	220 V	320 Pa	64 dB(A)	1300 x 1160 x 476 x 295~260 mm
FTC-H550N	5500 m3/h	86-91%	980W	220 V	320 Pa	64 dB(A)	1300 x 1160 x 476 x 295~261 mm
FTC-H600N	6000 m3/h	85-91%	1100W	220 V	330 Pa	65 dB(A)	1320 x 1160 x 550 x 328~289 mm

